

GREAT SOUND

at a fraction of the cost

NO FEEDBACK
REAL TONE
NEAT
and SMALL



ANTBUG

Violin Pickup

INCLUDED is your "ANTBUG", A 3 Metre Lead and Self adhesive velcro for your Violin Bridge.

INSTALLATION OF YOUR ANTBUG

Loosen all the strings, especially the G and D.

Lift left foot of the bridge and slide the round "BUG" underneath, flat side down, so that the wire is at the rear (tailpiece) end.

Make sure the foot of the bridge is totally on the bridge, then tighten up the strings.

Tune up!

The bridge should be between the nicks in the *f* holes and tilted slightly back.

Pass the plug inclosed in the velcro under the strings between the bridge and the tail piece. You can now fold the long part of the velcro over and press it onto the plug part, cut off any extra velcro.

Your lead has two jacks, the little jack is pushed into the Bug's plug (hold the plug steady as you push it in). Now wind some of the lead around your chin rest or your shoulder rest, so that it can't be pulled out by accident.

The big plug goes into your Amp. or Mixer. **TURN DOWN FIRST!!**

Bass and Treble should be flat. Gradually turn up while plucking a string.

You will soon find the ideal volume, sometimes a little Bass boost or Treble cut is necessary to get a perfect tone.

Tone can be enhanced by using those little pedals that guitarist have, (digital delay is fun) but most amps and PAs have reverb and thats more than enough

